

nGeniusONE Server

Pre-Integration of nGeniusONE Service Assurance Platform Software with Server Hardware to Accelerate and Simplify Deployment

HIGHLIGHTS

- Integrated and pre-configured hardware and software solution for the nGeniusONE™ platform
- Simplifies and speeds deployment with out-of-the-box implementation
- Specialized hardened and secure Linux® operating system optimized for scale and high performance
- Integrated remote management functions such as remote power off and on or crashed system recovery
- Provides a single-vendor solution with integrated hardware, operating system and the nGeniusONE platform software

Product Overview

nGeniusONE Server is an optimized server hardware platform that is pre-integrated and configured with the nGeniusONE Service Assurance platform software. The nGeniusONE Server is a high-performance and highly secure platform that enables the rapid and secure deployment of the nGeniusONE platform. NETSCOUT® integration of the nGeniusONE platform software with the server hardware provides a simplified solution that is available in two configuration options that offer flexibility and choice in server hardware capacity, enabling enterprises to right size server capacity to scale performance requirements. The pre-installed integrated solution enables IT to assure optimal performance and accelerate deployment for the nGeniusONE operating environment. The nGeniusONE server includes direct technical support from NETSCOUT's best-in-class support teams with 24x7 support services available under a single maintenance contract that minimizes the total cost of ownership of the nGeniusONE platform.

Product Capabilities

- Up to dual eight-core CPU, with 128 GB of memory with up to 10 TB of local storage.
- Flexible configuration options enable flexibility with varying performance capabilities.
- Customized, hardened and secure CentOS Linux Server 6.x 64-bit platform.
- Remote management capabilities support lights-out management and improves manageability.

Integrated Hardware and Software Simplify the nGeniusONE Platform Rollout and Deployment

The nGeniusONE hardware server and software solution simplifies the deployment process by providing everything needed in a single pre-configured, pre-licensed solution. The factory pre-integrated hardware and software minimizes the tasks typically associated with installation, configuration and maintenance, and significantly reduces time required to deploy the nGeniusONE platform.



Two nGeniusONE server hardware configurations are available:

- Standard** | Dual Six-Core Processor, 64GB Internal Memory, 4TB
- Enhanced** | Dual Eight-Core Processor, 128GB Internal Memory, 10TB

Specifications

Packet Capture Ports	4 Port 10/100/1000 BaseT
Storage	Standard: 4TB (4 x 1TB RAID 5) Enhanced: 10TB (5 x 2TB RAID 5)
Embedded OS	CentOS Linux 6.X 64 bit
Operating Environment	Secure hardened, embedded Linux operating system
CPU	Standard: Dual Six-Core 2.4GHz Enhanced: Dual Eight-Core 2.6GHz
Memory	Standard: 64 GB Enhanced: 128 GB
Rack Unit	2 Rack Unit (2RU)
Dimensions	3.4 in (87 mm) Height 17.5 in (444 mm) Width 29.6 in (684 mm) Depth
Weight	43 lbs (19.45 kg)
Power Rating (AC)	750W AC: 100-240VAC auto ranging, 50-60Hz
Maximum Consumption (AC)	10-5A
Heat Dissipation (AC)	2891 BTU/Hr
Fans	Hot swappable six-fan assembly unit
Operating Temperature	10° to 35°C (50° to 95°F)
Storage Temperature	-40° to 65°C (-40° to 149°F)
Operating Relative Humidity	10% to 80% (non-condensing twmax=26C)
Storage Relative Humidity	5% to 95% (non-condensing twmax=33C)
Operating Vibrations	0.26G at 5Hz to 350Hz in all orientations
Storage Vibration	1.87G at 10Hz to 500Hz for 15 minutes (all six sides tested)
Operating Shock	Half sine shock in all operational orientations of 31G +/- 5% with a pulse duration of 2.6ms +/- 10%
Storage Shock	Half sine shock on all six sides of 71G +/- 5% with a pulse duration of 2ms +/- 10%; square wave shock on all six sides of 27G with velocity change at 235 in/sec or greater
Operating Altitude	-15.2 to 3,048m (-50ft to 10,000ft)
Storage Altitude	-15.2 to 12,000m (-50ft to 39,370ft)
Regulatory and Agency Approvals	FCC (US only) Class A, ICES (Canada) Class A, CE Mark (EN55022 Class A, EN55024, EN61000-3-2, EN61000-3-3), VCCI (Japan) Class A, BSMI (Taiwan) Class A, C-Tick (Australia/New Zealand) Class A, SABS (South Africa) Class A, CCC (China) Class A, MIC (Korea) Class A, UL 60950-1, CAN/CSA C22.2 No. 60950-1, EN 60950, IEC 60950-1

Notes:

- 1) nGeniusONE Server does not include a monitor.
- 2) Please refer to the nGeniusONE Service Assurance platform data sheet for software product description and key features.
- 3) The nGeniusONE platform software may be purchased as a software-only solution supporting either Red Hat Enterprise Linux Server 5.x or 6.x 64 bit, CentOS Linux 6.x 64 bit or Windows® 2008 R2 standard edition.

Secured Environment Protects Packet Flow and Performance Management Data

nGeniusONE Server runs on a customized hardened and secure version of CentOS Linux Server 6.x 64 bit. To further harden security, access to the system and the data is restricted to only essential TCP/UDP ports. To minimize installation time and provide an optimized and highly secure operating environment, all current and necessary patches, upgrades, services and applications are pre-installed on the server hardware and all unnecessary services are disabled.

Remote Management Enhances System Manageability

nGeniusONE Server offers integrated remote management access, crashed system recovery, and power control functions for the server hardware. Remote management helps IT administrators remotely access the server to perform essential management tasks. With powerful, easy-to-use, remote management and configuration capabilities, the management server's management software alerts IT administrators when an issue occurs and enables streamlined local and remote server management. The server can be powered off or powered on and reset remotely which reduces or eliminates the need for physical site visits. IT administrators can observe a server boot sequence in its entirety with a progress indicator from the system BIOS that indicates boot sequence stages from power up to reset and provides tracing information for boot-related errors.

A Single Point of Contact Streamlines Support

The combined nGeniusONE Server and software solution simplifies support services. NETSCOUT provides a single point of contact for all hardware, operating system, and nGeniusONE platform support which eliminates the need to maintain multiple vendors, licenses and service contracts. This reduces complexity, and helps the operations team save time and reduce integration testing.



Americas East

310 Littleton Road
Westford, MA 01886-4105
Phone: 978-614-4000
Toll Free: 800-357-7666

Americas West

178 E. Tasman Drive
San Jose, CA 95134
Phone: 408-571-5000

Asia Pacific

17F/B
No. 167 Tun Hwa N. Road
Taipei 105, Taiwan
Phone: +886 2 2717 1999

Europe

One Canada Square
29th floor, Canary Wharf
London E14 5DY, United Kingdom
Phone: +44 207 712 1672

NETSCOUT offers sales, support, and services in over 32 countries.

For more information, please visit www.netscout.com or contact NETSCOUT at 800-309-4804 or +1 978-614-4000

© 2015 NETSCOUT SYSTEMS, INC. All rights reserved. NETSCOUT, nGenius, InfiniStream, Sniffer, nGeniusONE, ASI, Adaptive Service Intelligence and the NETSCOUT logo are registered or pending trademarks of NETSCOUT SYSTEMS, INC. and/or its affiliates in the United States and/or other countries ("NETSCOUT"). All other brands and product names are registered and unregistered trademarks are the sole property of their respective owners. Use of this product is subject to the NETSCOUT SYSTEMS, INC. ("NETSCOUT") End User License Agreement that accompanies the product at the time of shipment or, if applicable, the legal agreement executed by and between NETSCOUT and the authorized end user of this product ("Agreement"). NETSCOUT reserves the right, at its sole discretion, to make changes at any time in its technical information, specifications, service, and support programs.